



PVC Flexible Pipe

Corrugated Flexible conduit Pipe and fittings:

Corrugated Flexible conduit Pipes and fittings come in various material variants to suit various applications. For wiring purposes, these conduits are manufactured in variants based on the final application.

Types and Application:

Polypropylene Flexible Conduits Ideal for environments requiring constant flexing and vibration resistance, these conduits display excellent flexibility. They are lightweight, easy to install, and temperature-resistant from -5°C to $+90^{\circ}\text{C}$, making them a perfect choice for various applications.

Steel Wire Reinforced Flexible PVC Conduits Featuring a soft PVC wall integrated with high tensile steel wire, these conduits are unaffected by inorganic acids, alkali, and saline water. They are perfect for electrical wiring in buildings, machinery, and healthcare equipment, with temperature resistance ranging from -5°C to $+60^{\circ}\text{C}$.

PVC FLEXIBLE PIPE

HSN Code: 39173100

Colors available:

- Grey
- white
- Black

(Special colors available on order)

Features:

- Fire retardant
- Light weight
- Corrosion resistant
- Highly Stretchable
- High bending performance
- High abrasion resistance



DIMENSION OF PVC FLEXIBLE PIPE

Size (in mm)	Tolerance on Outside Diameter (in mm)	Maximum Outer Diameter (in mm)	Minimum Inside Diameter (in mm)
20	0.3	20	14.1
25	0.4	25	18.3
32	0.4	32	24.3
40	0.4	40	31.2
50	0.5	50	39.6



PP CORRUGATED FLEXIBLE CONDUIT

Sl No.	Product Code	Nominal Size (in mm)	Standard Packing	
			Mtr/Coil	Mtr/Bag
1	NOR61O1	20	30	600
2	NOR61O2	25	30	600
3	NOR61O3	32	30	600
4	NOR61O4	40	20	200
6	NOR61O5	50	15	150



STEEL WIRE REINFORCED FLEXIBLE PVC CONDUITS

Sl No.	Product Code	Nominal Size (in mm)	Standard Packing	
			Mtr/Coil	Mtr/Bag
1	NOR62O1	20	30	180
2	NOR62O2	25	30	120
3	NOR62O3	32	30	120
4	NOR62O4	40	30	90
6	NOR62O5	50	30	60



CORRUGATED FLEXIBLE CONDUIT GLAND

Sl No.	Product Code	Nominal Size (in mm)	Standard Packing
			Nos./Bag
1	NOR63O1	20	100
2	NOR63O2	25	100
3	NOR63O3	32	40
4	NOR63O4	40	25
5	NOR63O5	50	20

